

**§ 153.16 Requirements for foreign flag vessel permits.**

To have its Certificate of Compliance endorsed to carry a cargo listed in Table 1, a foreign flag vessel must:

- (a) Have an IMO Certificate, if the flag administration issues IMO Certificates, endorsed with the name of the cargo and meet any specific requirements in this subpart that the Commandant (G–MSO) may prescribe; or
- (b) Meet the requirements of this subpart and § 30.01–5(e) of this chapter.

[CGD 73–96, 42 FR 49027, Sept. 26, 1977, as amended by CGD 82–063b, 48 FR 4781, Feb. 3, 1983; CGD 81–052, 50 FR 8733, Mar. 5, 1985; CGD 81–101, 52 FR 7780, Mar. 12, 1987; CGD 95–027, 61 FR 26008, May 23, 1996]

**§ 153.30 Special area endorsement.**

The Coast Guard endorses the Certificate of Inspection of a United States ship allowing it to operate in special areas if the ship owner—

- (a) Requests the endorsement following the procedures in § 153.8;
- (b) Shows that the ship meets the design and equipment requirements applying to ships operating in special areas contained in Regulations 5, 5A, and 8 of Annex II and the Standards for Procedures and Arrangements.

[CGD 81–101, 52 FR 7780, Mar. 12, 1987]

**§ 153.40 Determination of materials that are hazardous.**

Under the authority delegated by the Secretary of Transportation in 49 CFR 1.46(t) to carry out the functions under 49 U.S.C. 1803, the Coast Guard has found the following materials to be hazardous when transported in bulk:

- (a) Materials listed in Table 30.25–1 of this chapter.
- (b) Materials listed in Table 151.05.
- (c) Materials listed in Table 1.<sup>1</sup>
- (d) Materials listed in Table 4 of Part 154.
- (e) Materials that are NLSs under MARPOL Annex II.
- (f) Liquids, liquefied gases, and compressed gases, that are—
  - (1) Listed in 49 CFR 172.101;

<sup>1</sup>Those hazardous material cargoes designated Category A, B, C, or D in Table 1 are also Noxious Liquid Substances under Annex II and the Act to Prevent Pollution from Ships, 33 U.S.C. 1901 *et seq.*

- (2) Listed in 49 CFR 172.102; or
- (3) Listed or within any of the definitions in subparts C through O of 49 CFR part 173.

(g) Those liquid, liquefied gas, and compressed gas materials designated as hazardous in the permissions granted under § 153.900(c).<sup>2</sup>

[CGD 81–101, 52 FR 7780, Mar. 12, 1987]

**Subpart B—Design and Equipment**

GENERAL VESSEL REQUIREMENTS

**§ 153.190 Stability requirements.**

Each vessel must meet the applicable requirements in Subchapter S of this chapter.

[CGD 79–023, 48 FR 51009, Nov. 4, 1983. Redesignated by CGD 81–101, 52 FR 7780, Mar. 12, 1987]

**§ 153.201 Openings to accommodation, service or control spaces.**

(a) Except as allowed in paragraph (b) of this section, entrances, ventilation intakes and exhausts, and other openings to accommodation, service, or control spaces must be located aft of the house bulkhead facing the cargo area a distance at least equal to the following:

- (1) 3 m (approx. 10 ft) if the vessel length is less than 75 meters (approx. 246 ft).
- (2) L/25 if the vessel length is between 75 and 125 meters (approx. 246 ft and 410 ft).
- (3) 5 m (approx. 16.5 ft) if the vessel length is more than 125 meters (approx. 410 ft).

(b) Fixed port lights, wheelhouse doors, and windows need not meet the location requirements specified in paragraph (a) of this section if they do not leak when tested with a fire hose at 207 kPa gauge (30 psig).

[CGD 81–078, 50 FR 21173, May 22, 1985]

**§ 153.208 Ballast equipment.**

(a) Except for the arrangement described in paragraph (b) of this section

<sup>2</sup>The Coast Guard continues to propose in the FEDERAL REGISTER any addition of these designated hazardous materials to one of the tables referred to in paragraphs (a) through (d).